


BALI 4

SL-UW-BA4-RGB	Luminaire:
Report No:	Voltage(V): 23.800
Test No:	Current(A): 0.371
LampCAT: :	Power (W): 8.800
Lamp flux(lm): -1.0	PF: 1.000
Number of Lamps: 0	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

Photometric Results

Lumens(lm): 662.62
Efficiency(%): 0.00%
Lumens(lm)/Power(W): 75.30
Central intensity(cd): 2687.286
Maximum intensity(cd): 3003.282
Angle of maximum intensity: C=45.0 γ =0.0
Beam Angle(50%Imax): [H]Left=12.0 Right=9.6
[V]Left=12.5 Right=9.5
Field angle(10%Imax): [H]Left=23.7 Right=19.5
[V]Left=23.2 Right=20.2
IES Classification : TypeI
Longitudinal Classification : VeryShort
Cut Off Classification : FullCutoff
Max Cd(At 90°Vert) : 0.1016064
Max Cd(80 to 90°Vert) : 3.048192
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire
Street Side DownWard Lumens: - -of lamp 45.10%of Luminaire
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire
House Side DownWard Lumens: - -of lamp 54.90%of Luminaire



C45(Max): —————
C0/C180: —————
C90/C270: —————

