

---

## BETIS WW

---



LumCAT: BETIS WW	Luminaire:
Report No:	Voltage(V): 241.000
Test No:	Current(A): 0.064
LampCAT: :	Power (W): 13.040
Lamp flux(lm): -1.0	PF: 0.832
Number of Lamps: 0	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

---

## Photometric Results

---

Lumens(lm): 572.50  
Efficiency(%): 0.00%  
Lumens(lm)/Power(W): 43.90  
Central intensity(cd): 2671.131  
Maximum intensity(cd): 2685.356  
Angle of maximum intensity: C=45.0  $\gamma$ =0.0  
Beam Angle(50%Imax): [H]Left=10.2 Right=9.3  
[V]Left=9.0 Right=10.8  
Field angle(10%Imax): [H]Left=24.9 Right=25.1  
[V]Left=24.7 Right=25.3  
IES Classification : TypeI  
Longitudinal Classification : VeryShort  
Cut Off Classification : FullCutoff  
Max Cd(At 90°Vert) : 0.2032128  
Max Cd(80 to 90°Vert) : 0.6096384  
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire  
Street Side DownWard Lumens: - -of lamp 51.02%of Luminaire  
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire  
House Side DownWard Lumens: - -of lamp 48.98%of Luminaire



C45(Max): —  
 C0/C180: —  
 C90/C270: —

