

---

## BETIS M WW

---



LumCAT: BETIS M WW	Luminaire:
Report No:	Voltage(V): 240.900
Test No:	Current(A): 0.088
LampCAT: :	Power (W): 19.090
Lamp flux(lm): -1.0	PF: 0.899
Number of Lamps: 0	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

---

## Photometric Results

---

Lumens(lm): 996.49  
Efficiency(%): 0.00%  
Lumens(lm)/Power(W): 52.20  
Central intensity(cd): 3179.163  
Maximum intensity(cd): 3259.432  
Angle of maximum intensity: C=45.0  $\gamma$ =0.0  
Beam Angle(50%Imax): [H]Left=14.2 Right=12.5  
[V]Left=12.6 Right=13.8  
Field angle(10%Imax): [H]Left=30.6 Right=29.3  
[V]Left=29.3 Right=30.3  
IES Classification : TypeI  
Longitudinal Classification : VeryShort  
Cut Off Classification : FullCutoff  
Max Cd(At 90°Vert) : 0.1016064  
Max Cd(80 to 90°Vert) : 0.4064256  
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire  
Street Side DownWard Lumens: - -of lamp 48.91%of Luminaire  
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire  
House Side DownWard Lumens: - -of lamp 51.09%of Luminaire



C45(Max): —————  
 C0/C180: —————  
 C90/C270: —————

