


CITY12 WW

SL-WW-C12-WW	Luminaire:
Report No:	Voltage(V): 23.900
Test No:	Current(A): 0.611
LampCAT: : name	Power (W): 14.600
Lamp flux(lm): -1.0	PF: 1.000
Number of Lamps: 1	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

Photometric Results

Lumens(lm): 864.42
Efficiency(%): 0.00%
Lumens(lm)/Power(W): 59.21
Central intensity(cd): 4566.548
Maximum intensity(cd): 4591.714
Angle of maximum intensity: C=45.0 γ =0.0
Beam Angle(50%Imax): [H]Left=11.7 Right=9.2
[V]Left=9.4 Right=11.6
Field angle(10%Imax): [H]Left=21.6 Right=18.3
[V]Left=19.3 Right=21.5
IES Classification : TypeI
Longitudinal Classification : VeryShort
Cut Off Classification : FullCutoff
Max Cd(At 90°Vert) : 0.8388608
Max Cd(80 to 90°Vert) : 4.82345
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire
Street Side DownWard Lumens: - -of lamp 47.36%of Luminaire
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire
House Side DownWard Lumens: - -of lamp 52.64%of Luminaire



C45(Max): —————
C0/C180: —————
C90/C270: —————

