


REAL10 WW

SL-WW-R10-WW	Luminaire:
Report No:	Voltage(V): 24.000
Test No:	Current(A): 1.025
LampCAT: : name	Power (W): 24.600
Lamp flux(lm): -1.0	PF: 1.000
Number of Lamps: 1	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

Photometric Results

Lumens(lm): 1174.67
Efficiency(%): 0.00%
Lumens(lm)/Power(W): 47.75
Central intensity(cd): 6575.620
Maximum intensity(cd): 6707.741
Angle of maximum intensity: C=315.0 γ =0.0
Beam Angle(50%Imax): [H]Left=10.4 Right=10.1
[V]Left=9.4 Right=11.1
Field angle(10%Imax): [H]Left=19.6 Right=19.6
[V]Left=19.0 Right=20.0
IES Classification : TypeI
Longitudinal Classification : VeryShort
Cut Off Classification : FullCutoff
Max Cd(At 90°Vert) : 0.2097152
Max Cd(80 to 90°Vert) : 1.572864
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire
Street Side DownWard Lumens: - -of lamp 50.86%of Luminaire
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire
House Side DownWard Lumens: - -of lamp 49.14%of Luminaire



C315(Max):
C0/C180:
C90/C270:

