


REAL10 RGB

LumCAT: SL-WW-REAL10 RGB	Luminaire:
Report No:	Voltage(V): 24.000
Test No:	Current(A): 1.400
LampCAT: :	Power (W): 33.600
Lamp flux(lm): -1.0	PF: 1.000
Number of Lamps: 0	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

Photometric Results

Lumens(lm): 595.39
Efficiency(%): 0.00%
Lumens(lm)/Power(W): 17.72
Central intensity(cd): 1486.908
Maximum intensity(cd): 1571.953
Angle of maximum intensity: C=45.0 γ =0.0
Beam Angle(50%Imax): [H]Left=16.2 Right=13.3
[V]Left=14.0 Right=14.7
Field angle(10%Imax): [H]Left=31.6 Right=28.7
[V]Left=29.1 Right=30.9
IES Classification : TypeI
Longitudinal Classification : VeryShort
Cut Off Classification : FullCutoff
Max Cd(At 90°Vert) : 0.1016064
Max Cd(80 to 90°Vert) : 2.844979
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire
Street Side DownWard Lumens: - -of lamp 46.87%of Luminaire
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire
House Side DownWard Lumens: - -of lamp 53.13%of Luminaire



C45(Max):
C0/C180:
C90/C270:

