


SIENA WW

SL-IO-SI-WW30	Luminaire:
Report No:	Voltage(V): 240.100
Test No:	Current(A): 0.024
LampCAT: :	Power (W): 2.600
Lamp flux(lm): -1.0	PF: 0.438
Number of Lamps: 1	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

Photometric Results

Lumens(lm): 116.57
Efficiency(%): 0.00%
Lumens(lm)/Power(W): 44.84
Central intensity(cd): 391.119
Maximum intensity(cd): 391.119
Angle of maximum intensity: C=0.0 γ =0.0
Beam Angle(50%Imax): [H]Left=14.1 Right=13.1
[V]Left=12.8 Right=15.0
Field angle(10%Imax): [H]Left=27.4 Right=26.1
[V]Left=25.7 Right=27.5
IES Classification : TypeI
Longitudinal Classification : VeryShort
Cut Off Classification : FullCutoff
Max Cd(At 90°Vert) : 0.1048576
Max Cd(80 to 90°Vert) : 0.2097152
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire
Street Side DownWard Lumens: - -of lamp 49.00%of Luminaire
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire
House Side DownWard Lumens: - -of lamp 51.00%of Luminaire



C0(Max):
 C0/C180:
 C90/C270:

