


SIENA RGB

SIENA RGB 3in1

Report No:	Voltage(V): 23.900
Test No:	Current(A): 0.147
LampCAT: :	Power (W): 3.500
Lamp flux(lm): -1.0	PF: 1.000
Number of Lamps: 0	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0

Photometric Results

Lumens(lm): 44.59
Efficiency(%): 0.00%
Lumens(lm)/Power(W): 12.74
Central intensity(cd): 113.088
Maximum intensity(cd): 119.692
Angle of maximum intensity: C=270.0 γ =5.0
Beam Angle(50%Imax): [H]Left=14.1 Right=15.2
[V]Left=14.6 Right=14.4
Field angle(10%Imax): [H]Left=29.8 Right=31.1
[V]Left=30.1 Right=30.1
IES Classification : TypeI
Longitudinal Classification : VeryShort
Cut Off Classification : FullCutoff
Max Cd(At 90°Vert) : 0
Max Cd(80 to 90°Vert) : 0.2032128
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire
Street Side DownWard Lumens: - -of lamp 40.29%of Luminaire
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire
House Side DownWard Lumens: - -of lamp 59.71%of Luminaire



C270(Max):
C0/C180:
C90/C270:

