
TUNA WW

SL-UW-TU-WW	Luminaire:
Report No:	Voltage(V): 24.300
Test No:	Current(A): 0.448
LampCAT: : name	Power (W): 10.800
Lamp flux(lm): -1.0	PF: 1.000
Number of Lamps: 1	Ballast type:
Length(mm): 0	Width(mm): 0
Phm Type: C	Height(mm): 0



Photometric Results

Lumens(lm): 447.47
Efficiency(%): 0.00%
Lumens(lm)/Power(W): 41.43
Central intensity(cd): 1812.284
Maximum intensity(cd): 1862.315
Angle of maximum intensity: C=45.0 γ =0.0
Beam Angle(50%Imax): [H]Left=12.2 Right=10.6
[V]Left=12.3 Right=10.2
Field angle(10%Imax): [H]Left=25.0 Right=24.5
[V]Left=25.4 Right=24.0
IES Classification : TypeI
Longitudinal Classification : VeryShort
Cut Off Classification : FullCutoff
Max Cd(At 90°Vert) : 0
Max Cd(80 to 90°Vert) : 1.148932
Street Side UpWard Lumens: - -of Lamp 0.00%of Luminaire
Street Side DownWard Lumens: - -of lamp 49.17%of Luminaire
House Side UpWard Lumens: - -of lamp 0.00%of Luminaire
House Side DownWard Lumens: - -of lamp 50.83%of Luminaire

Equipment:
Temperature(°C): 0.0

Date: 2013-12-28
Humidity(%): 0.0%

Operator: Opr
Distance(m): 10.22



C45(Max):
C0/C180:
C90/C270:

